



***The Beak is designed to work in a wide variety of work place applications.***



- Overall width . . . . . 46 inches
- Overall height . . . . . 28 inches
- Overall fork width . . . . . 26 inches
- Overall fork length . . . . . 39 inches
- Jaw opening distance . . . . . 38 inches
- Gripping force (approx) . . . . . 5000 pounds  
(depends on input pressure)
- Material . . . . . high-strength, steel plate
- Weight . . . . . 520 pounds
- Shipping weight (approx) . . . . . 560 pounds

The Beak's bottom shoe, with it's patented shape, increases the skid loaders break out force while the powerful top jaw maintains a solid grip on the load.



***Built with quality parts; The Beak can withstand the harshest job environments.***

**Easy Hook Up**

Flat-face couplings, quickly connect to most skid-steer loaders and does not require "Hi-Flo" hydraulic system.



**Custom Built, Heavy-Duty Cylinder**

The 3 inch cylinder is held in place with 1-1/4 inch diameter heat treated pins and the 1- 1/2" cylinder rod has black "Nitro" surface treatment for extended rod life. With 12 inches of stroke, The Beak easily opens to its full 38" potential.

The Beak is built for strength and is a "must-have" among contractors for concrete removal, waste management, rock and tree handling or moving steel drums, pipes, logs, tires, pallets or even cars.

